

File Name: canon bjc 240 manual.pdf Size: 1479 KB Type: PDF, ePub, eBook Category: Book Uploaded: 5 May 2019, 20:58 PM Rating: 4.6/5 from 685 votes.

Status: AVAILABLE

Last checked: 8 Minutes ago!

In order to read or download canon bjc 240 manual ebook, you need to create a FREE account.

Download Now!

eBook includes PDF, ePub and Kindle version

<u>Register a free 1 month Trial Account.</u>

Download as many books as you like (Personal use)

<u>Cancel the membership at any time if not satisfied.</u>

Join Over 80000 Happy Readers

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with canon bjc 240 manual . To get started finding canon bjc 240 manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

canon bjc 240 manual

Please do not offer the downloaded file for sell only use it for personal usage. Looking for other manual. Document preview No preview for this item!For this no need registration. May be help you to repair. You could suffer a fatal electrical shock. Instead, contact your nearest service center. Note! To open downloaded files you need acrobat reader or similar pdf reader program. In addition, Also some files are divu so you need divu viewer to open them. These free programs can be found on this page needed progs If you use opera you have to disable opera turbo function to download file. If you cannot download this file, try it with CHROME or FIREFOX browser. Eredetileg a fej dugulasa miatt nem nyomtatott. A fejet sikerult teljesen kitisztitani, minden jarat tiszta, fuvokakon nincs serules. Elektromosan kimerve a fejet teljesen normalis ertekek, szoval nincs zarlat sehol. A patronokat felismeri, tintaszinteteket latja, fejtisztitast elvegzi. Nyomtataskor a statuszablakban semmilyen hibakod nincs, teljesen normalis, nyomtat is, viszont a papirra egy csepp tinta nem kerul. A hasznalt tinta tartaly meg nem ert el kritikus erteket, a biztonsag kedveert visszaallitottam 20% os telitettsegre, az sem hasznalt. Probaltam vadonatuj patronokkal, tobbszori melytisztitassal, hogy toltse fel ujra a fejet. Kb. a tintak felet elhasznalta, latszik is, hogy mar lucskos a fej, de semmit nem nyomtat, meg a fuvokatesztre sem. Probaltam gyari eredeti patronokat atteni egy masik nyomtatobol, felismeri, tisztitja, de nem nyomtat veluk sem. Itt elakadt a tudomany, barmi otletet szivesen veszek. Canon IR 1600 Sziasztok! Van egy Canon IR 1600 tipusu fenymasolom, ami evek ota hibatlanul mukodik. Regebben kodolva volt a hasznalata, de mar hosszu ideje csak en hasznalom kod nelkul. Ma veletlenul programozaskor bekapcsoltam az azonosito rendszeret. Mit lehet ilyenkor tenni Mi a megoldas Minden tanacsot elore is koszonok. Udv. KumiSzeretnek segitseget kerni!http://www.first-classlogistics.com/image/upload/dyson-dc08-service-manual-download.xml

• canon bjc 240 manual, canon bjc 240 manual, canon bjc 240 manual download, canon bjc 240 manual pdf, canon bjc 240 manual downloads, canon bjc 240 manual free.

Minap a cimben emlitett nyomtatot hasznalni szerettem volna de sajnos nem tudtam mert a Fejet keresnek a fenti nyomtatohoz. Similar manuals You can write in English language into the forum not only in Hungarian. This page requires Javascript. Modify your browsers settings to allow Javascript to execute. See your browsers documentation for specific instructions. To install your download click on the name of the downloaded file.Scroll down to see your support options. You can also click one of these links to search our extensive Knowledge Base or visit the Canon Community Forum. The driver may be included in your OS or you may not need a driver. Recommended Drivers File Name Date File Size Optional Drivers File Name Date File Size Recommended Software File Name Date File Size Optional Software File Name Date File Size Warranty repair or replacement shall not extend the original warranty period of the Product. A dated proof of purchase is required at the time of warranty service. A copy of your dated bill of sale will satisfy this requirement. This warranty does not cover any accessories, or any consumables, such as paper or ink cartridges, as to which there shall be no warranty or replacement. Repairs of such Canon brand peripheral equipment shall be governed by the terms of the Separate Warranty. The sole warranty, if any, with respect to such nonCanon brand items is given by the manufacturer or producer thereof. Without limiting the foregoing, dropping the Product, scratches, and abrasions will be presumed to have resulted from misuse, abuse or failure to operate the Product as set forth in the users manual or other documentation for the Product. If the problem cannot be corrected over the telephone, and you elect the InstantExchange option, a reference number will be issued to you. You will be asked for the Product serial number and other information pertaining to your Product and for a shipto location for

the replacement Product must include street address.<u>http://www.hotelsinlansdowne.com/userfiles/cub-cadet-5252-owners-manual.xml</u>

After receipt of the replacement Product with instructions and a prepaid waybill, follow the enclosed instructions on how to ship your product to the Canon USA repair facility. Your Product must be returned in the shipping carton in which the replacement Product was packed and include the reference number, A COPY OF YOUR DATED PROOF OF PURCHASE BILL OF SALE, and a complete explanation of the problem.Canon USA does not guarantee same day shipment in the event of the occurrence of factors beyond its reasonable control. The replacement Product you receive may be a refurbished or reconditioned unit and will be covered for the balance of the period remaining on your original limited warranty. Scroll down to easily select items to add to your shopping cart for a faster, easier checkout. Visit the Canon Online Store Tired of trying to make your handwriting legible in order to illustrate a point. For your next important meeting, you can make impressive charts and graphs with these clear, overhead transparencies, printed right from your Canon Color Bubble Jet printer. Package includes 50 sheets. Optimize output resolution to create nearphotographic images. This paper is great when you want highquality color output to produce winning reports and eyecatching graphics. Use with genuine Canon Photo Inks for true photoquality output. Package includes 100 sheets. Lastmanuals provides you a fast and easy access to the user manual CANON BJC240. We hope that this CANON BJC240 user guide will be useful to you. All software is licensed AS IS, as described in the license agreement enclosed with the software media. Further, CCSI reserves the right to make changes in the specifications of the products described in this manual at any time without notice and without obligation to notify any person of such changes. Trademarks. Start your print operation. Chapter 3. Using Canons Specialty Papers.

This section provides guidelines for printing on Canons Specialty Papers and describes special procedures required for High Resolution Paper, Fabric Sheets, Banner Paper, and Glossy Photo Paper and Cards. Specialty Paper GuidelinesThese instructions provide important information regarding how to achieve the highest print quality with these papers. Follow these guidelines r When automatically feeding transparencies or back print film, remove each sheet after it is delivered.Media type Canon Glossy Photo Paper or Cards Canon Fabric Sheets Canon Transparencies Canon Back Print Film Drying time 10 minutes 1 hour 15 minutes 15 minutesChapter 3. Paper HandlingDust and dirt may accumulate on the film resulting in spotty printing.Do not remove papers from their protective packaging until you are ready to use them.Chapter 3. Paper HandlingChapter 3. Paper Handling. Cut the banner at a crease according to the length you need. Load the first sheet. Paper HandlingAdjust the printer location. Paper HandlingSet up the Printer Driver. Start printing. G2 GlossaryLines per inch. The measurement used in describing the number of lines that will print within one vertical inch. Most printing is done in 6 or 8 lpi. Manual feed. A method of feeding paper to the printer one sheet at a time. Noise level. See dBA. Page orientation. Refers to the direction of print on the page. Printing across the length of a page is called landscape orientation. Paper thickness lever. The green lever located inside the printer, which you adjust as necessary to accommodate different BJ Cartridges, paper thicknesses, and graphics densities. Parallel interface. In any way cant Lastmanuals be held responsible if the document you are looking for is not available, incomplete, in a different language than yours, or if the model or language do not match the description. Lastmanuals, for instance, does not offer a translation service. I cant be sure how well the floppy works.

Learn more opens in a new window or tab This amount is subject to change until you make payment. For additional information, see the Global Shipping Programme terms and conditions opens in a new window or tab This amount is subject to change until you make payment. If you reside in an EU member state besides UK, import VAT on this purchase is not recoverable. For additional information, see the Global Shipping Programme terms and conditions opens in a new window or tab Delivery times may vary, especially during peak periods and will depend on when your payment clears opens in a new window or tab. Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens in a new window or tab Learn More opens is intended. This item may be a floor model or an item that has been returned to the seller after a period of use. See the seller's listing for full details and description of any imperfections. I cant be sure how well the floppy works.Contact the seller opens in a new window or tab and request a postage method to your location. Please enter a valid postcode. Please enter a number less than or equal to 1. Sellers may be required to accept returns for items that are not as described. Learn more about your rights as a buyer. opens in a new window or tab Youre covered by the eBay Money Back Guarantee if you receive an item that is not as described in the listing. We may receive commission if your application for credit is successful. Terms and conditions apply. Subject to credit approval. We may receive commission if your application for credit is successful. All Rights Reserved. User Agreement, Privacy, Cookies and AdChoice Norton Secured powered by Verisign.

You may find documents other than justWe keep our list of direct Canon driver and firmware links uptodate so they are easy to find when you need them. Service manuals usually include printed circuit boards, block diagrams, exploded views, assembly instructions and parts catalog. Its invaluable source of information for everyone looking to repair their unit. You should look for Owners Manual. After placing order well send You download instructions on Your email address. Please try again. Please try again. Then you can start reading Kindle books on your smartphone, tablet, or computer no Kindle device required. Register a free business account If you are a seller for this product, would you like to suggest updates through seller support To calculate the overall star rating and percentage breakdown by star, we don't use a simple average. Instead, our system considers things like how recent a review is and if the reviewer bought the item on Amazon. It also analyzes reviews to verify trustworthiness. The BJC7000 Series printers offer excellent print quality and fast print speed using both color and black inks. We are certain you will be satisfied with this advanced Bubble Jet technology. This chapter. To find a dealer near you, call the Canon Referral Service at 18008484123. If supplies are not available from your local dealer you can order directly from Canon by calling 18003852155. Canon does not prohibit the use of thirdparty inks and the use of thirdparty inks does not invalidate the products limited warranty. However, Canon cannot guarantee the quality or performance of your printer when you are using inks from other suppliers. Canon Canada Customer support for Canadian residents is available 24 hours a day seven days a week at 18002631121 In other countries contact your Canon Dealer. If you do not have access to the Web, you can call Canon see page 14. See your Quick Start Guide for details.

The exact steps for printing a document may vary depending on the application program you are using. Refer to your software applications documentation for the exact printing procedure. If the Print Setup option does not appear in the File menu for your application, refer to the users manual supplied with the application. Auto To print photos or graphics at higher than normal printing quality. You see three tabs. o Quality o Color. The computer will be able to prepare the print file faster. See your Windows documentation for instructions. If you will be printing text in black ink only, enable Monochrome on the Print tab. Print draft documents in Monochrome rather than Color or Auto. Limit the number of colors on each page. You can stack paper in the sheet feeder to load it automatically, or you can manually feed one sheet at a time. Be sure to test a type of paper before you purchase a large quantity. Slide the o Align the edge of the paper with the right edge of the sheet feeder. Remove the page right away and allow the ink to dry. Printing On Envelopes You can stack up to 15 envelopes in the sheet feeder or you can manually feed envelopes are recommended. When you are ready to print on envelopes, follow these steps to stack envelopes in the sheet feeder. You can

also manually feed envelopes one at a time. Start your o Make sure the printer is on. Dust and dirt may accumulate on the film resulting in spotty printing. This takes about one hour. Printing On a Fabric Sheet o Make sure the paper support and paper output tray are extended. Set up the o In the Paper tab, select A4 for the Paper Size. This may prevent the print head unit from returning to the home position on the right and being capped, which may cause the print head to dry out. Perform the following maintenance, as necessary, to keep your printer in good operating condition.

You can use this pattern to check the operation of your printer and your print quality. See the sample print the printout on page 46. Nozzle o If any portion of the Nozzle Check Pattern is incorrect, clean the Check print head. See page 47 for details. Pattern. See the next section for details. Cleaning the Print Heads From Windows If you are using Windows, you can execute print head cleaning from the Control tab in the BJC7000 Printer Driver. Start the o Now click the first Print Head Cleaning icon. If the results of the Nozzle Check Pattern are not satisfactory, repeat these four steps in the following order until the pattern is satisfactory 1. Clean the print head. If the problem has not been corrected after deep cleaning the print head four or five times, replace the print head. BJ Cartridge Guidelines. You can replace the BJ tank without replacing the print head unit when you run out of any of the color inks. Use the BCI61 Color BJ Tank with the BC61 Color BJ Cartridge only. Spilled ink can stain any surface. Open BJ cartridges and BJ tanks carefully, and follow the guidelines presented here to protect against spilled ink. When switching from the BC61 Color BJ Cartridge to the BC62 Photo BJ Cartridge or vice versa, be sure to replace the entire unit. Never attempt to force the cartridge holder to the left manually. Wait a few minutes for the print head to cool down, then press the CARTRIDGE button again. Then remove the cap and tape. Insert the o If you are inserting a BC60 Black BJ Cartridge, insert it into the new BJ left side of the cartridge holder. cartridge. Now perform the print head alignment procedure see the Quick Start Guide for details. Every time you replace a BI cartridge, its a good idea to adjust the print head alignment to ensure optimum print quality. You may want to place it in a. Press the o The printer automatically starts cleaning the print heads and the CARTRIDGE POWER light blinks.

The storage box is for the BC61 Color BJ Cartridge or BC62 Photo BJ Cartridge only. Transporting the Printer If you plan to move the printer from one location to another, or if you want to store it, follow these steps. Turn off the. Cut the paper so that it. An opened BJ cartridge or BJ tank that is not installed in the printer or in the Ink Cartridge Storage Box may leak, and the print head may dry out. This chapter also contains information to help you solve printer problems. It covers a few basic problems and describes how to clear a paper jam. For complete problem solving information, be sure to use our support services. Attempting to repair the printer yourself may void the limited warranty as to that repair. If possible, remove the jammed sheet and press RESUME. If this does not clear the jam, follow these steps Press the o Turn off the printer. In the event of major changes in the contents of this manual over a long or short period, Canon will issue a new editions of this manual. QY81352000 BJC4300 SERVICE MANUAL, Rev.0 II. CONTENTS CHAPTER 1 MAJOR CHANGES This chapter explains the main differences between BJC4300 and BJC4400. CHAPTER 2 SERVICE MANUAL This chapter explains the main differences between the SERVICE MANUAL of the BJC4300 and BJC4400. Color BJ Cartridge Drop modulation technology has been adopted. Allow enough space for the printer to be used with ease. For banner printing leave a space about the size of an A4size paper in front of the printer. Also allow enough space at the back of the printer to set the banner paper. Set the paper selection lever before loading the paper. TABLE 31 QUICK **REFERENCE FOR SETTING Media Thickness Lever Paper Feed Flap Black.** Paper Support Supports the stack of paper loaded in the cut sheet feeder. The logic section converts the data from the interface into print signals or printer operation signals and drives the BJ cartridge and motors while monitoring the status of the sensors.

Sensor RESUME TH1 PC2 to 3 CARTRIDGE Pickup Roller Sensor 22.11MHz. Builtin CPU The 16bit

CPU operates in synchronization with a 20 MHz external clock input. It operates in synchronization with an external 22.11 MHz external clock input. Rubbing Section of Clutch Rubbing Section of Frame Spring and Clutch Gear and Paper Lifting Plate About 12 mg FLOIL G311S About 6 mg FLOIL G311S Rubbing Section of Cam Gear About 12mg FLOIL G311S. All circuit diagrams, lubrication, disassembly, replacement, reassembly parts, printer troubleshooting, adjustment, printer repair are provided in PDF. Troubleshooting is described according to problem descriptions as well as error indications by the status indicator, Appendix Block diagrams, location and signal assignment, Circuit diagrams.Service Manual Printers Canon BJC7000, BJC7004 Contents Safety and Precautions, Product Specifications, Operating Instructions, Technical Reference, Maintenance.Contents Product specifications, Maintenance, operation, Troubleshooting This part explains how to resolve problems of the unit, and contains information on how to locate and replace serviceable units and parts.Parts catalog, Circuit Diagram. Service Manual Desktop Page Laser Printer Canon LBP1260 Contents General description, Operation avd timing, The mechanical system Disassembly, Reassembly and adjustment procedures, Installation, Maintenance and servicing, Troubleshooting, Appendix General timing chart, General circuit diagram, PSB circuit diagrams.Parts catalog LBP1760, LBP1760e. Circuit Diagram LBP1760, LBP1760e.Parts catalog LBP3000, LBP2900 series. Circuit Diagram LBP3000, LBP2900 series. Contents Product description, Technical reference, Disassembly and assembly, Maintenance and inspection, Troubleshooting, Appendix. Page 6 CHAPTER 2 CHAPTER 2Page 8 Part 2 Product Specifications BJC4400Page 12 Part 2 Product Specifications BJC4400Allow enough space for the printer.

Page 14 Part 3 Operating Instructions BJC4400Page 15 BJC4400 Part 3 Operating InstructionsPage 16 CHAPTER 4 BJC4400 Part 4 Technical ReferencePage 18 Part 4 Technical Reference BJC4400Page 20 Part 4 Technical Reference BJC4400Page 21 BJC4400 Part 4 Technical Reference. Page 22 CHAPTER 5 BJC4400 Part 5 MaintenancePage 25 Part 5 Maintenance BJC4400. Cautions aler t you to w a ys to av oid injur y to y ourself, damage to the printer, or the loss of v aluable data. Use this button when y ou wish to enlarge the screen you are vie wing. Click the desired item to jump to the topic. Print Planet is a ser vice mark of Canon Computer Systems, Inc. Microsoft and Windows are registered trademarks of Microsoft Cor poration in the U.S. and other countries. Do not make an y changes or modi. Do not attempt to use the pr inter in an y way not described in this manual as this could result in unforeseen printer faults or cause a. If ammable solv ents come in contact with electrical components inside the pr inter, such substances could cause a.Do not use ammable spr a ys near the pr inter. Fibers or dust entering the pr inter could cause a re. K eep the power outlet f or the printer free of all obstacles so you can unplug the pow er cord at any time. Do not attempt to plug the pow er cord into the power outlet or unplug the pow er cord when your hands are wet. This could cause an electric shock. This could cause a.If you detect smok e, unusual smells or strange noises around the printer, immediately unplug the pow er cord. Continuing to use the printer in these circumstances could cause a. Do not use ammable solv ents such as alcohol, benzene or thinners. If ammable solv ents come in contact with electr ical components inside the printer, such substances could cause a. The printer contains moving parts that could cause injury. If a child inadv er tently licks a BJ car tridge or ink tank or ingests any ink, consult a physician immediately.

Auto Sheet Feeder Holds sheets of paper or other media for printing. Cartridge Lock Lever Unlocks the cartr idge holder so you can remov e and replace the BJ car tridge. Click the OK b utton. BJ Backgr ounder The BJ Backg rounder is displa yed in the lo wer right cor ner of the screen. Y ou can cancel or pause the pr int job. Click the Print b utton. Pr inting begins. The f ollowing screen appears during pr inting. The paper output tra y can be raised while you are not printing. Y ou can also use Canon Bubble Jet P aper. The original image is re versed mirrored when printed. Y ou can obtain a Photo Card pr inted o v er its entire area by printing the image so that it e xtends bey ond the perf orations and then trimming off the unwanted white margins. Ideal for printing photographs or

business documents that include large n umbers of color illustrations and graphs. A maximum of six sheets can be printed at one time. By setting the pr int area to e xtend bey ond the perf orations, y ou can use this media type to print cards without white margins. Howe ver, if the printed paper curls, or ink does not dr y quic kly, remo ve each sheet as it comes out of the printer. T o av oid paper feed prob lems, do not use doub le. For Windows user s For Macintosh users F or optimum reproduction of all the color tones, mak e sure that the Media T ype setting is correct for the media y ou hav e loaded in the printer. Enabled When the Whole Page setting is enabled, the Photo Optimizer adjusts multiple photogr aphic images appear ing on the same page separately. Use this setting when any trimmed or rotated images are contained in the page. The f ollowing BJ car tridges consist of a pr int head and ink tank sealed in one unit. When you purchase e xtra ink tanks, specify the BCI21 Color Ink T ank or BCI21 Black Ink T ank. Make sure the printer is connected to the pow er outlet. 1 Open the front cov er. Remov e the orange protective cap and tape.

5 Set the BJ car tridge into the car tridge holder. Then lower the car tridge loc k le ver until it loc ks into place. To use the printer with your computer, you m ust install the pr inter driv er. F or instr uctions on installing the printer dr iv er, refer to the Ouick Start Guide. The Pr inter Proper ties dialog bo x opens. The Printer Proper ties dialog box opens. The print settings in the Printer Proper ties dialog bo x allow. T o con r m all def ault settings, click the Adv anced button after selecting the icon. If this inf or mation is not correct, clic k on the P age La yout tab and mak e the correct selections. Use the online help f eature to. Y ou can now use the BJC2100 f or pr inting. When only cer tain pages of a document are to be printed, click the F rom button and enter the. Select the icon that is closest to your document type and intended results. The Current Settings shows the name of the selected icon, along with inf or mation on the Halftoning and Color Correction f or the selected Print Mode.When you position the cursor ov er a given item, a brief explanation of that item appears in a balloon.On the print ser ver, select the pr inter driv er called BJC2100. F rom the print ser ver, the progress of printing can be con. A list of documents that are currently being printed as well as those in the print queue is display ed. Note, ho we ver, that the owner of the client machine and the o wner of the document must be the same. Look f or spra yed ink, paper dust, or scr aps of paper especially around the platen.Print the Nozzle Check P atter n when your printouts are streak ed or the color tones are not correct, or after print head cleaning. BC21e Color BJ Cartridg e or BC22e Photo BJ Cartridge Black BJ Cartridge If the patter n is brok en or missing, or a speci.Cleaning the print head consumes ink so clean the print head only when necessary. Make sure that the printer is plugged in.

The f ollowing sections describe how to star t print head cleaning from the pr inter driv er. The Cleaning begins. Open the Printer Proper ties dialog box, clic k the Maintenance tab and then click the clean paper f eed rollers icon. Select P age Setup from the File menu, then click Utilities and clic k the F eed Rollers Cleaning icon. 4 When you are prompted to con. Some application programs ha ve a setting in the print dialog box that allows y ou to enable or disab le color printing. Check that the setting is enabled in the application program. Open the printer dr iv er dialog bo x and select the pr int mode best suited f or the print job. Y ou may not be able to achie v e satisfactory performance with an ink tank that has been re.It is recommended that you use ink tanks speci. Open the printer dr iv er dialog bo x and select the pr int mode best suited f or the print job in the Choose Pr int Mode bo x under the Main tab. If the printout does not match the document display ed on the screen when you print a cer tain. Rebuild the le and print it again. If you print on paper larger than the page size selected in the printer driver, the page is printed in the top left cor ner. If Scaled Printing is set for enlargement in the printer driver, the document is enlarged and printed in the bottom r ight corner, or cut off at the bottom or right edge of the paper. Make sure that the correct print side is f acing up when you load the media in the auto sheet f eeder. Mov e the Intensity setting pr int density to a low er setting and e xecute the print job again.Pr intouts may be stained by e xcess ink inside of the printer. If you are using plain paper, use another type of pr int media. T o minimize ink spread, use

High Resolution P aper, Glossy Photo P aper, or High Gloss Film.Remov e the plain paper, tur n it o ver, and load it in the auto sheet feeder again. If you print outside the recommended printing area, the pr int head may scratch the bottom edge of the page.

T o av oid problems, print only in the recommended printing area. Check the Halftoning setting in the Quality tab of the printer driver.Con r m whether or not a WPS driver is installed in y our system.Gradation appears streak ed.The printer tur ns on automatically as soon as you plug it into the power outlet. A print job may not start if y ou have selected the wrong printer driver f or the print job. Check that " Canon BJC2100 " is displayed in the Name entry box of the Print dialog box. If you are using the P arallel interf ace to connect your printer, set your printer port to LPT1.Remov e the BJ car tr idge and check the print head. Make sure the paper rest is installed on the printer at all times. Y ou can set up to 5 env elopes in the auto sheet f eeder. If the printer port setting is not identical to the interface connected to the printer, an error message appears. Attempting to print from a Windows 3.1 application program installed on the Windows 98 or Windows 95 platform ma y cause an error. An error may occur if there is not enough free space av ailab le on the hard disk. Check the amount of free space on the hard disk. There may be a problem with the printer driver. One of the f ollowing messages may be displayed. Delete any unneeded. Check that the required amount of memory is allocated to the application program. If there is not enough memory installed, install more memory. Make sure that the printer cab le is securely fastened to the computer and the printer. The Quic k Star t Guide provides stepb ystep instructions f or installing the printer dr iv er. The installation program may not ex ecute successfully if it is star ted with other applications running in the background. Bef ore you run the installation program again, shut do wn all other application programs. The Install Me First CDROM may be damaged. On the Windows desktop, doubleclic k the My Computer icon then doubleclick the CDR OM icon.